

## Ultra-thin 14×17" LED Film Viewer

# FV-2014

- ▶ 16.1" × 13" window size (fit 17" × 14" film)
- ▶ Electronic light mask in vertical and horizontal
- ▶ Rugged viewer feet, support any angle and wall mount
- ▶ Smart cooling system, Fan with temperature depended



MAX.  $L \geq 120,000 \text{Cd/m}^2$

$g=0.9$

$\sigma'=0.9$

### Fashion design and Reliable mechanism

FV-2014 looks like a fashion LCD, but it is a really High luminance LED Industrial film viewer. It combines our newest electronic technology and most reliable LED driven circuit. Thanks to it, this viewer can view film density up to 4.2 H/D, and can be operated 24 hours continuously.

### Electronic light mask

FV-2014 not only support 14" \* 17" film, but also support any film size. Because FV-2014 do have a strong LED switch control. Under its help, you can switch on or off any parts of area in the viewer window.

### Specification:

Max Luminance: $\geq 120,000 \text{Cd/M}^2$ (376,800Lux)	Uniformity: $g=0.90$
Diffusion Factor: $\sigma'=0.90$	Viewer window: 335×410mm (13×16.1 inch)
Surface temp. rise $\leq 20^\circ\text{C}$ After 12 hours continues maximum luminance	Power: 85-264VAC 47~63Hz. (changed by a switch)
Dimension: 51×41×7cm 20.1×16.1×2.8 inch (L×W×H)	Weight: 7.4Kg (16.3 lbs)

Stand on the table



Mount on the wall



New Design of film holder (More convenient)



### WenZhou LuCheng NDT Equipment Corp.

Manufacturer of NDT equipments  
RM.308,Kang Yuan South Building XinCheng Road,  
325000 WenZhou, P.R.China.

Tel.:0086-577-88293040  
Fax:0086-577-88259689  
Web:www.Lcndt.net  
E-mail:Lcndt@163.com