

Spot viewer LED Film Viewer

FV-2018 IRIS

- ▶ **Adjustable IRIS spot viewer**
- ▶ **Extreme high luminance, 2 level for option**
- ▶ **300,000Cd/m² or 1,000,000Cd/m² (Developing)**
- ▶ **Compact Design, only 2.3Kg**



MAX. L ≥ 300,000Cd/m² (1,000,000 Cd/m² for optional)

Extreme High Luminance

Two level of Luminance For Choose:

- FV-2018 IRIS : 300,000 Cd/m² Film: 4.5D
- FV-2018 IRIS Max: 1,000,000Cd/m² Film:5.0D

IRIS adjustable light mask

Spot view size can be adjust from φ5mm - φ100mm

Standard Package:

Spot LED viewer
Power adapter with 2.5m cable
Manual (English)
Test report (English)
Warranty Card (English)

Programmable “Stand by Luminance”

* Stand by Luminance: The luminance of the viewer when you release the foot pedal

Programmable Range : From 0% to 10%

Specification:

Max.Luminance: ≥ 300,000Cd/m² (942, 000Lux)

Optional: ≥ 1,000,000Cd/m² (314,000,000Lux)

Viewer window: φ 5mm - φ 100mm
(0.2inch - 3.9inch)

Uniformity: g=0.95 Diffusion σ'=0.95

Weight: 2.3Kg (5.1 lbs)

Dimension: 27×21×16cm
10.6×8.3×6.3 inch (L×W×H)

Power: 85-264VAC 47~63Hz.